

### Specifications

Type	VJ-1628MH	
Printing system	On-demand piezo print head	
Print head height	Automatic (max thickness: 5/8 inch)	
Max media width	64 Inches / rigid and roll media	
Printable width	Max: 63.6 in. Minimum: 7.2 in / rigid and roll media	
Ink	Type	MP31 ink
	Ink set	Up to 8 colors CMYKx2, CMYKWhWh
	Volume	500ml bag
	No. of slots	8
Print resolution	1440/1080/720dpi (Total 6 modes)	
Interface	Ethernet (10BASE-T/100BASE-TX)	
Media measurements	Rigid media: Max length 48 in. (with standard media tables) Min. length 7.9 in. / 33lbs or less * To print on rigid media, the optional media feeding table is required. Roll media: Ø 5.9" / 2" & 3" / 66lbs or less	
Media-drying system	Blower heater system: 1200W x 2	
Power requirements	AC100-240V ± 10%, 50/60Hz ± 1Hz	
Noise at printing	65dB or less	
Printable environment	Temperature : 68-82.4F Humidity: 40-60%RH	
Electrical power consumption	Operation status: 300W, 2400W/ 2lines at AC200-240V 300W, 1200W, 1200W/ 3lines at AC100-120V	
Dimensions (WxDxH) / weight	<b>Printer with stand : 106.22" x 32.20" x 51.26"   106.22" x 107.5" x 51.26" (including feeding table)</b> Printer: 369.3 lbs. Stand: 72.8 lbs. Media feeding table F/R: 94.8lbs. each 66lb take-up system: 46.30lbs.   88lb take-up system: 39.68lbs.	
Packing size (WxDxH)	Printer: 113.39" x 45.28" x 33.46" / 581.36lbs.   Stand: 88.39" x 15.55" x 9.84" / 79.37lbs. Media feeding table F/R: 69.69" x 45.67" x 8.46" / 125.66lbs. each 66lb take-up system: 92.91" x 13.31" x 8.27" / 63.93lbs.   88lb take-up system: 111.02" x 17.72" x 15.35" / 52.91lbs.	
Take-up system	Standard 66lb included   Optional Heavy Duty 88lb take-up system available	
RIP software	VerteLith bundled with FlexiDESIGNER MUTOH Edition 21, a \$2,199.00 value	

Data in the specifications are subject to change without notice.